

More  
**Air**  
For Less  
Power



**HEAVY DUTY WATERCOOLED VERTICLE & OPPOSE  
BALANCE HIGH PRESSURE AIR & GAS OIL FREE COMPRESSOR**



- | Water cooled, Rugged cast iron design, Ideal for heavy duty & continuous operation
- | 100% Oil free & Lubricated Compressors.
- | Lower operating cost, Simple maintenance
- | Easy accessibility of spares at economical price

### Specifications

Model	Motor HP	Comp. Rpm.	Piston		Maximum		Length	Dimension (Inch)			Weight kgs
			Displacement Cfm	fad	Working Pressure kg/cm <sup>2</sup> g	psig		Width	Height lub	Height NL	
CT7x5V	30	750	164	110	8.80	125	20	22	56	68	620
CT8x5V	40	750	215	143	7.00	100	20	22	56	68	680
CT8x7V	50	650	260	180	9.50	135	20	28	66	70	818
CT9x7V	60	650	330	240	7.70	110	22	28	66	79	840
CT11x7V	75	650	498	319	7.00	100	25	28	75	88	1355
CT12&7x70B	125	750	680	547	8.80	125	142	49	75	75	2150
CT16&10x70B	250	750	1216	1045	8.80	125	151	49	86	86	2600

Other three & four Stage high pressure models also available  
 Upto 95 kg/cm<sup>2</sup>g. for Air & Gas Application

### Features

Forged Crank Shaft & Connecting Rod, Precision main & Crank Pin Bearings.

Cylinders constructed with large cast in-water jackets & Specially Designed intercoolers for dimensional stability & better cooling under continuous operation

Comptech Kit Package comes with built in single point water Inlet/Outlet connection and air outlet connection. It requires very little time and labour during installation. The Standard Package includes a compact skid mounted compressor/belt guard, electric motor, starter and control panel, after cooler, non return valve with optional Air Dryer, compressed air filter and Air Receiver. It's ready to use. Just plug in to power supply.



### Specification

Model	Motor HP	No. of stages	FAD cfm	Working kg	Compressor rpm	Dimension (in cm)		
						L	W	H
CTBO25/30	30	2	96	25	531	260	155	160
CTBO42/40	40	3	117.6	42	430	260	155	160
CTBO42/50	50	3	148	42	530	260	155	160
CTBO42/60	60	3	155	42	640	260	155	160
CTBO42/75	75	3	196	42		478	198	224
CTBO42/100	100	3	257	42		478	198	224
CTBO42/125	125	3	287	42		478	198	224
CTBO42/150	150	3	376	42		478	198	224
CTBO42/175	175	3	419	42		478	198	224

**REACH PNEUMATICS**

# 42/2, 6TH Cross, 5th Main,

Malleswaram, Bangalore-560003. India.

Phone: +91 80 23469620, Telefax: +91 80 23465570. Cell: 9845075620

e-mail: [reachp@vsnl.com](mailto:reachp@vsnl.com) reachpneumatics@gmail.com