



More
Air
For Less
Power



Rotary Screw Air Compressor

- Intelligent Microprocessor Controller
- Three Stage Air oil separator
- Low Specific power consumption
- Less noise level and ease of maintenance.





Compressed air is a type of clean and environmental friendly energy. Frank's goal is to make the use of this energy easier by proposing Solution and Systems that are the result of a careful analysis of the needs of all potential users, distributors and their satisfaction. We have widened and completed our range of air compressors, and accessories for aimed solutions.

Integrated Screw Aired

To Maintain maximum performance, efficiency and ease of service. The airend, interconnecting piping and separation systems have all been integrated into one simple design. Integration of the compression module eliminates leaks and pressure losses to increase efficiency and performance.



Compressor Imported from Italy



Integrated Screw Aired

Integration of the compression module eliminates leaks and pressure losses to increase efficiency and performance.



Micro Processor Control System

Intelligent micro computer control system. The LCD can show present temperature, working pressure, accumulative working time, malfunction, etc.



Three stage Separator

Service & maintenance are made extremely simple through three stage spin-on filtration and separator cartridges.



Quiet Operation

Oversized, high efficiency cooling air blower. Provides sound levels as low as 78 dBA.



Poly-V Belt Drive

Premium drive system applies patented automatic tensioning to eliminate belt stretch and increase air output.



Model	Max Working pressure In Bar	Motor		Cu.m / hr	CFM	Noise dB (A)	Weight in kg.	LWH In mm
		HP	KW					
FFC-05/8/BASE	8	5	4	34.8	20.5	65	93	480x570x650
FFC-05/8/220	8	5	4	34.8	20.5	65	193	1500x570x1250
FFC-07/8/BASE	8	7.5	5.5	41.4	24.4	66	93	480x570x650
FFC-07/8/220	8	7.5	5.5	41.4	24.4	66	193	1500x570x1250
FFC-10/10/BASE	10	10	7.5	59	34.8	68	122	580x650x800
FFC-10/10/500	10	10	7.5	59	34.8	68	322	1500x650x1400
FFC-15/8/BASE	8	15	11	99	58.3	68	230	870x760x1035
FFC-15/8/500	8	15	11	99	58.3	68	430	1500x760x1635
FFC-15/10/BASE	10	15	11	86	52.6	68	230	870x760x1035
FFC-15/10/500	10	15	11	86	52.6	68	430	1500x760x1635

For any other capacity contact factory. Specifications are subject to change without notification

REACH PNEUMATICS

42/2, 6TH Cross, 5th Main, Malleswaram, Bangalore-560003. India.

Phone: +91 80 23469620, Telefax: +91 80 23465570. Cell: 9845075620

e-mail: reachp@vsnl.com reachpneumatics@gmail.com